

Coolani

3D Airflow
Comfortable Sleep Mode
Cold Air Prevention
Timer
Self-diagnosis
Auto Restart
Automatic Operation
Auto Swing
Filter Dirty Alarm
Dehumidifying
Soft Start
Low voltage startup
Golden Fin

Features: Standard Optional

Window type

AIR CONDITIONERS CATALOGUE



145V low voltage start up

The unit could operate from 145V to 265V, which is suitable for unstable power supply areas.



Soft start

Through adjusting the startup voltage and capacitor of compressor to lower its starting current, enabling the compressor to start smoothly, restraining the impact on distribution network and postponing the wastage on compressor.



Self-diagnosis

Once abnormal operation or parts failure happen, the unit will shut off automatically to protect the system. Meanwhile it will indicate protection or error code for fast service.



Fresh air supply ventilation

The unit can introduce a certain percentage of fresh air to satisfy the fresh air requirement.



R32

Model			GJC09AF-E6RNB3A	GJC12AG-E6RNB3A
Function			Cooling	Cooling
Capacity	Cooling	Btu/h	9212	12454
	Heating	Btu/h	-	-
SEER		W/W	5.2	5.4
Energy Class Cool			A	A
Power Supply		Ph,V,Hz	1Ph,220-240V,50Hz	1Ph,220-240V,50Hz
Power Input	Cooling	W	782	1030
	Heating	W	-	-
Rated Current	Cooling	A	5.5	6.5
	Heating	A	-	-
Airflow Volume	Indoor	m^3/h	400/360/320	480/430/380
Sound Power Level	Indoor	dB(A)(SH/H/M/L)	50/48/46	50/48/46
	Outdoor	dB(A)(SH/H/M/L)	56/54/52	58/56/54
Outline Dimension	WxHxD	mm	560×375×710	660×428×700
Package Dimension	WxHxD	mm	623×425×806	739×515×793
Net Weight/Gross Weight	Indoor	kg	43/47	50/54
Loading Quantity	40'GP	sets	260	184
	40'HQ	sets	312	230

1.The product with * is under development, and the parameters are estimated， please refer to the value on nameplates.
2. Gree reserves the right to modify the specifications without prior notice. Please confirm the final specifications with sales representatives.